

Technická špecifikácia ventilátora VSM

typ	motor kW	množstvo vzduchu m ³ /hod	tlak Pa	otáčky ot./min	A mm	B mm	C mm	DN mm
VSM-031-0140-K	1,5	1340	2250	2840	691	596	371	140
VSM-028-0140-K	4	1340	2400	2850	738	672	402	140
VSM-035-0160-K	2,2	1730	2100	2820	716	636	406	160
VSM-031-0160-K	3	1730	2800	2850	760	696	430	160
VSM-028-0160-K	4	1730	4000	2880	841	764	457	160
VSM-040-0180-K	3	2200	2300	2850	726	621	456	180
VSM-035-0180-K	4	2200	3600	2880	799	690	483	180
VSM-031-0180-K	5,5	2200	4300	2880	858	765	583	180
VSM-031-0180-K	7,5	2200	5300	2880	858	765	583	180
VSM-045-0200-K	3	2700	2200	2850	756	646	476	200
VSM-040-0200-K	5,5	2700	2700	2860	815	716	582	200
VSM-035-0200-K	7,5	2700	4300	2880	872	762	602	200
VSM-031-0200-K	11	2700	5500	2900	954	833	652	200
VSM-050-0220-K	4	3300	2350	2880	786	666	522	220
VSM-045-0220-K	5,5	3300	3300	2860	862	744	602	220
VSM-040-0220-K	7,5	3300	3800	2880	786	666	522	220
VSM-035-0220-K	11	3300	5100	2880	977	852	602	220
VSM-056-0250-K	5,5	4230	2500	2860	816	676	622	250
VSM-050-0250-K	7,5	4230	2800	2880	872	734	642	250
VSM-045-0250-K	11	4230	4800	2900	932	797	692	250
VSM-040-0250-K	15	4230	5500	2920	985	851	704	250
VSM-071-0300-K	7,5	6100	2300	2880	871	716	692	300
VSM-063-0300-K	11	6100	3300	2900	942	784	742	300
VSM-056-0300-K	15	6100	4250	2920	1000	838	754	300
VSM-050-0300-K	18,5	6100	5200	2920	1067	906	792	300
VSM-080-0350-K	7,5	8350	2200	2900	869	722	772	350
VSM-071-0350-K	11	8350	2800	2900	992	812	772	350
VSM-063-0350-K	15	8350	3100	2920	1060	876	784	350
VSM-056-0350-K	18,5	8350	5100	2900	1138	967	784	350
VSM-071-0400-K	11	10900	2500	2900	1046	872	820	400
VSM-071-0400-K	15	10900	2800	2920	1046	872	858	400
VSM-071-0400-K	18,5	10900	3600	2900	1046	872	858	400